




INSTALLATION INSTRUCTIONS FOR
AM53758 FUEL TANK KIT
FOR JD340/S SNOWMOBILES




M66047 Instructions

1. Remove the hood and fuel tank cover.



2. Remove seat and alter as follows:
Cut out the front of the seat 2-3/4 inches from the top, 1-1/4 inches from each side and 2 inches in depth. This will allow the seat to conform to the NEW 10 gallon fuel tank.




3. Remove fuel line from tank and cap tank fitting to prevent fuel from draining out of tank.

NOTE: Use a short piece of fuel line with a 5/16 inch bolt threaded into line as a cap for the fuel tank fitting.

⚠ CAUTION: Gasoline is dangerous, even when mixed with oil. Avoid fires due to smoking or careless maintenance practices.

4. Disconnect strap securing fuel tank to tunnel and remove tank.
5. Rinse NEW fuel tank with fuel before installing to be sure tank is clean.
6. Install NEW 10 gallon fuel tank. Use care to prevent rubber pads on bottom of tank from being knocked off during installation. Use fuel tank cap from old tank on one opening of the new tank.



7. Route vent line under steering post, over and around support and secure line to steering support with tie strap.
8. Connect fuel line to tank and secure with clamp.
9. Install seat and hood. Fill tank with 50:1 mix of PREMIUM FUEL ONLY.

NOTE: If a new fuel tank cover for the 10 gallon tank is desired, order AM53759.